

Alarm Contacts




SD70, SD80, SD82

- For standard and tighter fitting applications.
- Sensitive "No stick" UL rhodium reed.
- Excellent choice for hollow metal doors.



SM35, SM35C

- Includes spacers, screws, and cover



FM 102

- Flange Mount with special adhesive & 18" leads


TANE ALARM PRODUCTS

Magnetic Contacts

Mfg #	Description	Type	Size	Gap	EZ #
FM102	Flange Mount	N.C.	1.33"L x .3"W x .53"H	1"	083083
SD70	Stubby Recessed	N.C.	3/4" X 080"	1-1/2"	083082
SD80	Stubby Recessed	N.C.	1" X 080"	1-1/2"	083080
SD82	Stubby Recessed	S.P.D.T.	1" X 080"	1-1/2"	083092
SM35	Standard Surface Mount	N.C.	2-1/2" x 1/2" x 1/2"	1" to 2"	083084
SM35C	Standard Surface Mount	S.P.D.T.	2-1/2" x 1/2" x 1/2"	1" to 2"	083582

Miscellaneous

Power Supplies & Transformers



BD2E & BE2G


- Stripped wire input (primary) leads, screw terminal/quick fit tab terminal output (secondary).
- Nipple locknut mount for box installation, complete with locknut and mounting bracket
- UL Listed, CSA Certified



BPD2E

- Ideal for electric strikes & cameras requiring up to 500 mA input.
- Center positive.
- cUL listed.

Mfg #	Type	Output	Amps	Volt Amps	EZ #
BD2E	Wire in Transformer	12VAC	1.67	20VA	084138
BE2G	Wire in Transformer	24VAC	1.67	40VA	084139
BPD2E	Plug in Power Supply	12VDC	.5		084134



BCONNECTORS

- B Connector has an outer shell of plastic with an inner sleeve of Beryllium copper plated with bright nickel
- Resistance: 10 mΩ initial
- Dielectric: 1000 V
- Strength of Joint: 9 lbs.
- Package of 1000



BCONNECTORS GELL

- As above but silicone filled for moisture filled environments.

Access Control & CCTV Cable Connectors

311



- Crimp-on connector for RG59/U cable.
- Crimp-on tools are required to affix connectors.



PP25

- 2 Piece barrel connector for low power applications using low voltage cable.
- Connections must be soldered.

TN50UG882



- Twist-on connector for RG59 cable CCTV systems.



5 554720 3

- Connector for Cat5E
- Requires Cat5E crimping tool.



PA-CBFBF

- BNC Female to BNC Female.
- Allows connection of 2 BNC Cables



PP CORD

- 3' Flying lead connector allows you to plug into a camera lead to enable power connection to the two wire leads.

TY8

- For tidying up cable installs..

Mfg #	Description	EZ #
311	Crimp on BNC Connector	091073
5 554720 3	RJ45 Network Connector	091074
BCONNECTORS	Standard	083089
BCONNECTORS GELL	Gel Filled	083090
PA-CBFBF	BNC Cable Joiner	090052
PP25	Barrel Connector	086651
PP CORD	Video Power Fly Lead	100524
TN50UG882	BNC Twist-on Connector	081046
TY8	8" Tie Wraps	083088