

MONARCH®

Grade 1 Rim Exit Device

- Reversibility: Rim devices are non-handed.
- 161 Cutout: covers stock hollow metal cutout. 910 & 912 Trims require cover plate.
- Latchbolt: 3/4" throw.
- Dogging: 1/2" turn cam.
- Doors: 1-3/4" thick standard wood or metal
- Projection: 2-1/2" maximum, 1-7/8" depressed.
- Size: For doors 2'5" to 3'0". For wider doors & narrow stile please see LSDA PD911 series
- ANSI: Certified ANSI A156.3 -1984 Grade 1 standards.
- UL listed for life safety.



19R EO

- Rim exit device is a single point latching device with deadlocking latch bolt

F19R

- Fire rated version

Mfg #	Fire Rated	EZ #
19R EO SP28 3	No	027178
F19R EO SP28 3'	Yes	011096

Exit Device Trim



910TP NL

910TP BE

912L NL

914KIL

Mfg #	Function	EZ #
910TP NL SP28	Entrance by thumbpiece only when released by key. Key removable only when locked.	036395
910TP BE SP28	Entrance by thumbpiece at all times	065297
912L NL DANE SP28RHR	Entrance by lever only when released by key. Key removable only when locked.	036393
912L NL DANE SP28LHR		036392
914KIL KD32D	Entrance by lever. Key locks or unlocks lever..	011105

Accessories



571

- Used on inactive leaf for device on active leaf of pair of doors without removable mullion.
- Keeps 2-5/16" backset

Trims & Accessories are interchangeable with LSDA PD911 Series of exit devices.

94253

- 12" extension rod for 19V & LSDA PD911V devices.
- Both ends tapped.
- All-thread included as connector

Mfg #	Description	EZ #
571 26D	Double Door Surface Strike	036396
94253 28	12" Vertical Rod Extension	011127